



SPECTRUM HOSE LTD

Handling the Pressure.....

Eolo L Ducting

A light weight and highly flexible Grey PVC ducting. For suction and discharge of air, fumes & saw dust. Suitable for use in Aerating and Conditioning plants



Construction: PVC duct reinforced with anti-shock rigid PVC spiral,
smooth inside surface, outside corrugated.

Temperature: -10° C + 50° C

Part Number	Inside Ø		Weight	Min Wall Thickness	Max Wall Thickness	Bending Radius	Vacuum	Roll Length
	mm	inch						
IHELL025	25	1"	150	0.8	2.5	30	2,5	50
IHELL030	30		190	0.8	2.6	35	2,5	50
IHELL032	32	1-1/4"	200	0.8	2.8	35	2	50
IHELL035	35		225	0.8	2.9	35	2	50
IHELL038	38	1-1/2"	250	0.8	3.0	45	2	50
IHELL040	40		270	0.8	3.0	50	2	50
IHELL045	45		340	0.8	3.1	55	2	50
IHELL050	50	2"	415	0.8	3.5	60	2	50
IHELL060	60		485	0.8	3.6	70	1,6	50
IHELL063	63	2-1/2"	505	0.8	3.6	70	1,6	50
IHELL070	70		560	0.8	3.8	90	1.5	50
IHELL076	76	3"	615	0.9	3.8	100	1,5	50
IHELL080	80		725	0.9	4.3	110	1,5	50
IHELL090	90	3-1/2"	825	0.9	4.5	125	1,4	30
IHELL100	100		940	0.9	4.6	140	1,3	30
IHELL102	102	4"	940	0.9	4.6	140	1,3	30
IHELL110	110		1065	1.0	5.0	150	1,2	30
IHELL120	120		1165	1.0	5.0	160	1	30
IHELL127	127	5"	1230	1.0	5.0	170	1	30
IHELL130	130		1260	1.0	5.0	170	0,9	30
IHELL140	140		1405	1.0	5.1	175	0,9	30
IHELL150	150	6"	1550	1.1	5.2	180	0,8	20
IHELL160	160		1725	1.1	6.0	190	0,7	20
IHELL180	180		1940	1.1	6.0	300	0,4	20
IHELL200	200	8"	2135	1.1	6.0	400	0,4	20
IHELL250	250	10"	3210	1.2	6.8	450	0,4	10
IHELL300	300	12"	3895	1.2	6.9	1000	0,3	10