



**SPECTRUM HOSE LTD**

*Handling the Pressure....*

## SAE 100 R6 HOSE

LOW PRESSURE HYDRAULIC LINES, FUEL OIL, ANTIFREEZE SOLUTIONS, AIR AND WATER. SPECIALLY DESIGNED FOR USE IN "PUSH ON" APPLICATIONS



**Tube** : OIL RESISTANT SYNTHETIC RUBBER

**Reinforcement** : ONE HIGH TENSILE TEXTILE BRAID

**Cover** : ABRASION, OZONE AND HYDROCARBON RESISTANT SYNTHETIC RUBBER.

**Constant operation** : -40 °C +100 °C (T max air = +70 °C)

**Ambient temperature** : -40 °C +80 °C

**Branding** : ALFAGOMMA FLEXOR 6 ID... - WP ... MPa (... PSI) - SAE 100R6-EN854 R6 -DN ... - Q/yr

PART NUMBER	I.D. mm	I.D. Inch	O.D. mm	WORKING PRESSURE. Psi	BURST PRESSURE. Psi	BEND RADIUS. mm	WEIGHT. Kg/m.
HHR6-03	4.5	3/16	12.0	400	1600	64	0.13
HHR6-04	6.0	1/4	13.1	400	1600	64	0.13
HHR6-05	8.0	5/16	14.3	400	1600	76	0.13
HHR6-06	9.5	3/8	15.9	400	1600	76	0.17
HHR6-08	12.7	1/2	19.8	400	1600	102	0.23
HHR6-10	16.0	5/8	23.0	350	1400	107	0.27
HHR6-12	19.0	3/4	26.9	300	1200	152	0.37