



SPECTRUM HOSE LTD

Handling the Pressure.....

ISO 7840 MARINE FUEL HOSE

A black rubber fire resistant fuel hose for use with permanent installations of inboard boat engines. Suitable for use with fuel with up to 50% Aromatic content, 15% oxygenated compound, biodiesel and ecological fuel. Complies with ISO 7840:2013 A1.



Construction: **Liner.** Smooth black synthetic rubber.
Reinforcement. High Strength textile yarn.
Cover. Black self-extinguishing rubber.

Temperature: -20°C to +80°C.

Identification: THOR® CARBOPOMP® MARINE FUEL ISO 7840:2013 A1 E10/B10 COMPATIBLE CE"

PART NUMBER	BORE (inches)	BORE (mm)	OUTSIDE DIAMETER (mm)	WORKING PRESSURE (bar)
IH7840006	1/4"	6.0	15	4.5
IH7840008	5/16"	8.0	16	4.5
IH7840010	3/8"	9.5	18	4.5
IH7840013	1/2"	12.5	21	3
IH7840016	5/8"	16.0	25	3
IH7840019	3/4"	19.0	29	3
IH7840025	1"	25.0	37	3
IH7840032	1-1/4"	32.0	44	3
IH7840035	1-3/8"	35.0	47	3
IH7840038	1-1/2"	38.0	52	3
IH7840051	2"	51.0	64	3