



SPECTRUM HOSE LTD

Handling the Pressure.....

Oil Suction & Delivery Hose. 10 Bar. (T6702)

A rubber Suction and Delivery hose for oil and petroleum products with up to 50% aromatic content.



- Construction :** **Tube:** Oil & Petrol resistant NBR.
Reinforcement: High Tensile Synthetic Textile, Steel Wire Helix.
Cover: Black, smooth conductive rubber, abrasion, oil, fuel, ozone and weather resistant. Flame resistant according TRbF – 131 – Teil 2 - § 5.5.
- Identification :** OIL S/D W.P. 10 BAR - 150 PSI
- Temperature :** -20°C to +70°C3

30 Bar Nominal Burst Pressure

| Part Number | Inside Diameter (Inch) | Inside Diameter (mm) | Outside Diameter (mm) | Maximum Working Pressure (bar) | Vacuum m/H2O | Min Bend Radius (mm) | Weight gr/mtr |
|-------------|------------------------|----------------------|-----------------------|--------------------------------|--------------|----------------------|---------------|
| IHT6702019 | 3/4 | 19 | 29 | 10 | 0.8 | 115 | 600 |
| IHT6702025 | 1 | 25 | 35 | 10 | 0.8 | 150 | 750 |
| IHT6702032 | 1-1/4 | 32 | 42 | 10 | 0.8 | 190 | 950 |
| IHT6702038 | 1-1/2 | 38 | 48 | 10 | 0.8 | 230 | 1100 |
| IHT6702045 | 1-3/4 | 45 | 55 | 10 | 0.8 | 270 | 1250 |
| IHT6702051 | 2 | 51 | 61 | 10 | 0.8 | 300 | 1400 |
| IHT6702060 | 2-3/8 | 60 | 71 | 10 | 0.8 | 360 | 1950 |
| IHT6702063 | 2-1/2 | 63 | 74 | 10 | 0.8 | 390 | 2050 |
| IHT6702076 | 3 | 76 | 88 | 10 | 0.8 | 450 | 2550 |
| IHT6702090 | 3-1/2 | 90 | 104 | 10 | 0.8 | 540 | 3500 |
| IHT6702102 | 4 | 102 | 118 | 10 | 0.8 | 600 | 4400 |
| IHT6702127 | 5 | 127 | 145 | 10 | 0.8 | 750 | 6100 |
| IHT6702152 | 6 | 152 | 172 | 10 | 0.8 | 915 | 8500 |